

An easy-to-use, web-connected 24-inch printer



More for your money

- Two printers in one. Print from A4/Letter to A1/D using the A3/B+ tray and 24-inch (610 mm) wide front-loading media roll
- Install your printer where it's most convenient and work where you want, thanks to Wi-Fi connectivity¹
- Take control of your print jobs by plotting them in-house, saving time and money
- Enable outstanding print quality and high productivity with Original HP inks and long-life printheads

Compact and easy to use

- Easily fit this printer—the smallest in its class—where you need it in your studio
- The intuitive, full-colour, 4.3-inch (109 mm) touchscreen simplifies navigation and printing
- Complete your work quickly and accurately, thanks to true print previews from the driver

Print from virtually anywhere²

- Use your Apple® or Android™ smartphone or tablet to print from virtually anywhere²
- Access and print projects when you're away from your studio, using HP Designiet ePrint & Share²
- Automatically save copies of your work to the cloud when you print using HP Designjet ePrint & Share²
- Email projects to your HP Designjet T120 ePrinter and print, thanks to its web connectivity features²

For more information, please visit hp.com/go/DesignjetT120

HP Designjet ePrint & Share allows you to print to your HP Designjet ePrinter from your Apple® or Android™ smartphone or tablet—helping you get work done even when you're away from the studio². hp.com/qo/eprintandshare

- Wireless performance is dependent on physical environment and distance from access point, and may be limited during active VPN connections. Supports IEEE 802.11 b/g.
- Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple® iOS or Android™ device and Internet connection are required. Data or connection charges may apply. Print times may vary. For more information visit hp.com/go/eprintandshare.

Technical specifications

	•		
Print	Line drawings³	70 sec/page on A1/D, 40 A1/D prints per hour	
	Colour images ⁴	Fast: 22.4 m²/hr (241 ft²/hr) on coated media Best: 2.3 m²/hr (25 ft²/hr) on glossy media	
	Print resolution	Up to 1200 x 1200 optimised dpi	
	Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in)	
	Technology	HP Thermal Inkjet	
	Ink types	Dye-based (C, M, Y); pigment-based (K)	
	Ink drop	5.5 pl (C, M, Y); 12 pl (K)	
	Printheads	1 (C, M, Y, K)	
	Line accuracy	+/- 0.1%5	
	Minimum line width	0.04 mm (0.0016 in) (HP-GL/2 addressable)	
	Guaranteed mini- mum line width	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁶	
Media	Handling	Sheet feed, roll feed, input tray, automatic cutter	
	Weight	$60\ to\ 280\ g/m^2$ (roll/manual feed); $60\ to\ 220\ g/m^2$ (input tray)	
	Size	Rolls: 279 to 610 mm (11 to 24 in)	
		Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in)	
		Standard sheets: A4, A3, A2, A1 (A, B, C, D)	
	Thickness	Up to 11.8 mil	
Memory	256 MB		
Connectivity	Interfaces (standard)	Fast Ethernet (100Base-T), Hi-Speed USB 2.0 certified, Wi-Fi	
	Print languages (standard)	HP PCL 3 GUI, JPEG	
	Printing paths	Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint	
	Drivers (included)	HP PCL 3 GUI driver for Mac OS X and Windows®	
Dimensions	Printer	987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)	
(w x d x h)	Shipping	1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)	
Weight	Printer	25.5 kg (56.2 lb)	
	Shipping	30 kg (66.1 lb)	
What's in the		ePrinter, printhead, introductory ink cartridges,	
box	quick reference guide, setup poster, startup software, power cord		
ranges	Operating temperature: 5 to 40°C (41 to 104°F)		
	Storage temperature: -25 to 55°C (-13 to 131°F)		
	Operating humidity: 20 to 80% RH		
Acoustic	Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)		
	Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)		
Power consumption	< 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 1200 mA max		
Certification	Safety	USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSE China (CCC), Mexico (NYCE)	
		Compliant with Class B requirements, including:	
	Electromagnetic	USA (FCC rules), Canada (ICES), EU (EMC/R&TTE Directives), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)	
	Environmental	Directives), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A	

Ordering information

Product	CQ891A	HP Designjet T120 24-in ePrinter
Accessories	B3Q35A	HP Designjet T120 24-in Stand
	B3Q36A	HP Designjet T120/T520 24-in Spindle
	J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server
Original HP printhead	C1Q10A	HP 711 Designjet Printhead Replacement Kit
Original HP	CZ129A	HP 711 38-ml Black Ink Cartridge
ink cartridges	CZ130A	HP 711 29-ml Cyan Ink Cartridge
	CZ131A	HP 711 29-ml Magenta Ink Cartridge
	CZ132A	HP 711 29-ml Yellow Ink Cartridge
	CZ133A	HP 711 80-ml Black Ink Cartridge
	CZ134A	HP 711 3-pack 29-ml Cyan Ink Cartridges
	CZ135A	HP 711 3-pack 29-ml Magenta Ink Cartridges
	CZ136A	HP 711 3-pack 29-ml Yellow Ink Cartridges
Original HP large format printing materials	C1860A	North America, HP Bright White Inkjet Paper Latin America (FSC® certified) ⁷ 🖧8
	C6035A	Europe, Asia 610 mm x 45.7 m (24 in x 150 ft)
	C6019B	HP Coated Paper (PEFC™ certified) ⁷ 🏰 610 mm x 45.7 m (24 in x 150 ft)
	C6029C	HP Heavyweight Coated Paper (PEFC™ certified) ⁷ ♣6 610 mm x 30.5 m (24 in x 100 ft)
	CZ987A	HP Premium Satin Photo Paper (FSC® certified) ⁷ 610 mm x 15.2 m (24 in x 50 ft)
Service and support	U1V95E	HP 3 year Next Business Day Onsite Support
	U1W29E	HP 3 year 4-hour response, 13x5 Onsite Support
	U1W34PE	HP 1 year Post Warranty, Next Business Day Onsite Support
	U6A00PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support

HP Designjet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services.

For more information, please visit <u>hp.com/go/designjetsupport</u>.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimised printing system to provide precise line accuracy as well as dark blacks.

For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see global BMG. com/hp.

- $^{\scriptscriptstyle 3}$ Mechanical printing time. Printed in Fast mode on plain paper with Original HP inks.
- ⁴ Mechanical printing time with Original HP inks.
- 5 +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and Original HP inks.
- ⁶ Measured on HP Matte Film.
- Fiscond of the Matter full.

 FSC® trademark license code FSC®-C017543, see <u>fsc.org</u>. PEFC™ trademark license code PEFC™/29-31-198, see <u>pefc.org</u>. Not all FSC®- or <u>PEFC™</u>-certified products are available in all regions.
- 8 Can be recycled through commonly available recycling programs.

















For more information, please visit

hp.com/go/DesignjetT120

© Copyright 2013-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a U.S. registered trademark of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

